

Load Restraints

**RAPID
DELIVERY**



SAFETY IS PARAMOUNT!

✓ Wherever loads must be restrained, ensure your safety with our polyester webbing lashings. Manufactured in accordance with BS5759:1987, we offer lengths, widths and load capacities to suit every industrial and commercial application.

Whatever your requirement is, please contact us

In addition to the popular range below, we can offer -

- Any webbing length
- Special end fittings
- Wear sleeves
- Special application designs
- Restraints up to 10 tonnes



Cam Fastener



Ratchet Fastener



Heavy Duty Ratchet



Delta Link / Claw Hook / S-Hook
End Fittings

Webbing Load Restraints

APPLICATION	CAPACITY (kg)	LENGTH (metres)	WIDTH (mm)	TENSIONER	END FITTING	ORDER REF	PRICE
ROOF RACK	330	3	25	CAM	ENDLESS	LSCE2503	£5.40
	330	5	25	CAM	ENDLESS	LSCE2505	£7.10
	250	3	25	CAM	CLAW HOOK	LSCC2503	£8.00
	250	5	25	CAM	CLAW HOOK	LSCC2505	£8.90
ROOF RACK AND TRAILER	800	3	25	L/D RATCHET	ENDLESS	LSRE2503	£6.60
	800	7	25	L/D RATCHET	ENDLESS	LSRE2507	£9.10
	600	3	25	L/D RATCHET	S-HOOK	LSRP2503	£9.60
	600	5	25	L/D RATCHET	S-HOOK	LSRP2505	£11.00
	600	7	25	L/D RATCHET	S-HOOK	LSRP2507	£12.40
	600	10	25	L/D RATCHET	S-HOOK	LSRP2510	£15.50
TRAILER AND GENERAL PURPOSE	2000	5	25	H/D RATCHET	ENDLESS	LSE2505	£10.50
	2000	7	25	H/D RATCHET	ENDLESS	LSE2507	£11.90
	1000	5	25	H/D RATCHET	CLAW HOOK	LSC2505	£11.70
	1000	7	25	H/D RATCHET	CLAW HOOK	LSC2507	£13.10
	4000	7	35	RATCHET	ENDLESS	LSE3507	£12.90
	2000	5	35	RATCHET	CLAW HOOK	LSC3505	£16.90
	2000	7	35	RATCHET	CLAW HOOK	LSC3507	£18.50
	2000	10	35	RATCHET	CLAW HOOK	LSC3510	£21.70
HEAVY DUTY	5000	4	50	RATCHET	CLAW HOOK	LSC5004	£16.70
	5000	6	50	RATCHET	CLAW HOOK	LSC5006	£18.40
	5000	8	50	RATCHET	CLAW HOOK	LSC5008	£20.00
	5000	10	50	RATCHET	CLAW HOOK	LSC5010	£21.70
	5000	12	50	RATCHET	CLAW HOOK	LSC5012	£23.40
	5000	4	50	RATCHET	DELTA LINK	LSD5004	£16.70
	5000	6	50	RATCHET	DELTA LINK	LSD5006	£18.40
	5000	8	50	RATCHET	DELTA LINK	LSD5008	£20.00
	5000	10	50	RATCHET	DELTA LINK	LSD5010	£21.70

i SAFE USE OF LOAD RESTRAINTS

- Always check the webbing for cuts and wear before use
- Use a minimum safety factor of double the load weight
- Never use twisted lashings
- Use correct end fittings for the application involved
- Never tie lashings together
- Store properly after use